

用途及特点

Application & Features

- 1、体积小、噪音低。
- 2、采用大油箱，降低了油温升，延长了真空油的更换时间周期。

1.Small dimensions,low noise.

2.The big oil tank prevents the oil temperature from going up and delays the changing revolution of

vacuum oil.



2XZ-2



2XZ-8B

型号 Model		XZ-0.5	XZ-1	2XZ-0.25	2XZ-0.5	2XZ-1	2XZ-2	2XZ-4	2XZ-8B	2XZ-15
抽速 Pumping speed:L/S		0.5	1	0.25	0.5	1	2	4	8	15
极限 Ultimate partial 分压强 Pressure (Pa)	气镇关 Without gas ballast	10	10	6×10^{-1}	$6 \times 10^{-2} (\leq 5 \times 10^{-4} \text{ Torr})$					
	气镇开 With gas ballast	—	—	—	≤ 6 ($\leq 5 \times 10^{-2} \text{ Torr}$)	≤ 1.3	$(\leq 1 \times 10^{-1} \text{ Torr})$			
转速 Speed (r. p. m.)		1400								
电机功率 Motor power (kw)		0.09	0.12	0.12	0.18	0.25	0.37	0.55	0.75	2.2
进气口直径 Gas inlet dia (mm)		6	8	10	15	15	25	25	40	40
工作温度 Operating temperature (°C)		90								
用油量 Oil capacity (L)		0.3	0.5	0.6	0.8	0.9	0.6	1.1	2.1	2.5
噪音 Noise: dB (A)		≤ 50	≤ 50	≤ 55	≤ 60	≤ 65	≤ 72	≤ 75	≤ 75	≤ 75
重量 Weight: (kg)		5	6	11	15	17	21	25	45	75